


Rail Car Rupture Disks

Features

- Ideal for Railroad tank cars
- Allows extended use for a full year without change-out regardless of number of trips logged
- Unaffected by virtually all corrosives except elemental Fluorine
- Provides maximum full bore venting capacity
- Supplied in two styles to fit either metal seated or fully rubber covered 2" AAR safety vents
- Both Model AC and RC carried in stock for immediate delivery
- Steel armored for added strength
- Flexible liner used on pressure side to automatically provide a degree of temporary reclosure after venting an overpressure incident





Model AC

Designed for fully rubber covered 2" safety vents without precise seats. This disk features a larger outside diameter.

Gasketing

Non asbestos on vent side VITON on pressure side

AAR 2" rubber covered safety vent accepts **ZOOK Model** AC Disk

VITON -TM DuPon



Models	Burst Rating▲ (psig)	Outside Diameter
RC60	60	
RC100	100	3-1/8"
RC165	165	

From each lot of ZOOK Rupture Disks, at least two disks are burst in the appropriate AAR safety vent to qualify burst rating as specified in AAR A5.03. Additionally, these disks have been qualified for -15% +0% tolerance per AAR A5.04

Models	Burst Rating▲ (psig)	Outside Diameter
AC60	60	
AC100	100	4-3/4"
AC165	165	



Rail-Car 012018

Visit us at www.zookdisk.com

SERVING AMERICA, CENTRAL SERVING EUROPE, **& SOUTH AMERICA**

16809 Park Circle Drive Chagrin Falls, Ohio 44022 **United States**

Toll Free: +1 800 543 1043 Phone: +1 440 543 1010 Fax: +1 440 543 4930 E-mail: sales@zookdisk.com

MIDDLE EAST & AFRICA

Navigation House, Bridge St. Killamarsh, Sheffield, S21 1AL United Kingdom

Phone: +44 (0) 1909 560999 Fax: +44 (0) 1909 560860 E-mail: sales.europe@zookdisk.com Fax: +1 905 681 8838

SERVING CANADA

4400 South Service Road Burlington, Ontario, L7L 5R8 Canada

Toll Free: +1 800 370 6057 Phone: +1 905 681 2885

SERVING ASIA PACIFIC

Unit No. 23A-05, Menara Landmark No.12, Jalan Ngee Heng 80000 Johor Bahru, Johor, Malaysia

Phone: +60 (7) 2910099 Fax: +60 (7) 2910096

